

Quality is in our nature

Additives - Oil

Eurol Hydraulic Tappet Valve

Oil additive aimed at reducing hydraulic tappet noise

Description

Eurol Hydraulic Tappet Valve additive is an additive developed to reduce hydraulic tappet valve noise. Eurol Hydraulic Tappet Valve additive is recommended for all engines equipped with hydraulic valve tappets. Eurol Hydraulic Tappet Valve additive increases the lubricant film between moving parts, quieting the movement of the tappets and making the car more comfortable to drive.

Oil canals are unblocked and the rattling noise, coming from the valve train, is reduced to a barely audible level after adding Eurol Hydraulic Tappet Valve additive to the engine oil.

Based on ashless technology, Eurol Hydraulic Tappet Valve additive is compatible with a wide range of engine oils, both mineral and synthetic based. 250ml of Eurol Hydraulic Tappet Valve additive is suitable for 4 to 6L of engine oil. Add 1 bottle of Eurol Hydraulic Tappet Valve additive to the crankcase and let the engine idle for 10 minutes.

Users should consult the Material Safety Data Sheet of Eurol Hydraulic Tappet Valve additive for information about storage and shelf life. Please ask Eurol Research & Development if any further information is required.

Physical properties

Density at 20°C	0.844 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	210.7 cSt	ASTM D 445
Viscosity, kinematic at 100°C	32.5 cSt	ASTM D 445
Flash point	218 °C	ASTM D 93
Pour point	-9 °C	ASTM D 97

E802321 Version 1.0, 19-01-2017